



DIMENSIONAIS (mm)				
d1	d3	d7	L3	L9
20,0	31,0	35,0	22,0	19,5
22,0	33,0	37,0	21,5	19,5
24,0	35,0	39,0	23,5	19,5
25,0	36,0	40,0	26,5	19,5
28,0	40,0	43,0	26,5	19,5
30,0	43,0	45,0	26,5	19,5
32,0	46,0	48,0	28,5	19,5
33,0	47,0	48,0	28,5	19,5
35,0	49,0	50,0	28,5	19,5
38,0	53,0	56,0	33,5	22,0
40,0	56,0	58,0	36,0	22,0
43,0	59,0	61,0	38,5	22,0
45,0	61,0	63,0	39,5	22,0
48,0	64,0	66,0	46,0	22,0
50,0	66,0	70,0	45,0	23,0
53,0	69,0	73,0	47,0	23,0
55,0	71,0	75,0	49,0	23,0
58,0	76,0	78,0	55,0	23,0
60,0	78,0	80,0	55,0	23,0
63,0	83,0	83,0	55,0	23,0
65,0	84,0	85,0	55,0	23,0
68,0	88,0	90,0	55,0	26,0
70,0	90,0	92,0	57,0	26,0

\*para outras medidas de eixo ou alojamento, consulte-nos.

LEGENDA
ELASTÔMEROS
SEDE ESTACIONÁRIA
SEDE ROTATIVA
PARTES METÁLICAS
OPERACIONALIDADE
PRESSÃO
10 kgf/cm <sup>2</sup>
9,8 bar
142,23 psi
VELOCIDADE
10 m/s
TEMPERATURA
- 20° C ~ 180° C